

## Hood

Ref.: AD996XC

### Product highlights

**Electronic soft touch controls** The access of function is simple, direct and intuitive for more comfort.

**Baffle filters** These baffle filters are attractive and effective in capturing grease. Total hood absorption power is maintained during operation. You can put them in dishwasher.

**Powerful extraction** A maximum of extraction in order to recycle air regularly and efficiently.

GENERAL	
Brand	BRANDT
Commercial code	AD996XC
EAN code	3660767975354
Customs code	84146000

FEATURES	
Product type	Wall decorative hood
Design type	
Width (cm)	90
Finishing	Stainless steel
Colour	Stainless steel
Air vented mode	Recycling or extracting air
Delivered in	Air extraction
Type of engine	
Total power of the motors (W)	
Number of motors	1
Motor location	In chimney
Delayed stop	
LED dimmer	
Fan quantity	1

PERFORMANCE	
Annual energy consumption (kWh)	
Energy efficiency class	
Discharge air flow (m <sup>3</sup> /h) speed mini	-32767
Max extraction rate (m <sup>3</sup> /h)	
Extraction rate with boost (m <sup>3</sup> /h)	
Min recirculation rate (m <sup>3</sup> /h)	
Max recirculation rate (m <sup>3</sup> /h)	
Recirculation rate with boost (m <sup>3</sup> /h)	
Min noise level (dB) (Extraction)	
Max noise level (dB) (acoustic pressure)	
Noise level with Boost (dB) (Extraction)	
Min noise level (dB) (recirculation)	
Max noise level (dB) (recirculation)	
Noise level with Boost (dB) (recirculation)	
Fluid dynamic efficiency class	
Light efficiency class	
Lighting efficiency (Lux)	
Grease filter efficiency class	

CONTROLS & LIGHTS	
Control type	Electronic soft touch controls
Number of speed positions (without booster)	4
Booster	
Filters saturation indicator	
Type of light	LED
Number of lights	2
Total power of the lamps (W)	

EQUIPMENT	
Type of functions	Delayed stop;Independent lighting;Filter saturation indicator;Speed;On/Off
Number of grease filters	
Grease filter material	Washable stainless steel
Accessories supplied	
Reference of charcoal filter	
Reference of recycling kit	
Optional accessories	Charcoal filter
Reference of engine	
Reference of the chimney extension	
Air outlet diameter (mm)	150
Deflector	
Non-return valve	Yes

## Hood

Ref.: AD996XC

### INSTALLATION

Fuse (A)	10
Voltage (V)	220-240
Frequency (Hz)	50
Other functions	
Dimensions of the product without chimney HxWxD (mm)	1020X900X500
Min-max chimney height (mm)	/
Dimensions of the packed product HxWxD (mm)	980X580X500
Net weight (kg)	18
Gross weight (kg)	21

### MANUFACTURING

Availability of spare parts (years)	15
Repair index	