

De Dietrich

Dishwasher

Ref.: DCJ422Q SX



Product highlights

Automatic Door Opening At the end of the drying cycle a special device opens slowly and automatically the doorsome centimeters to ensure a perfect drying which can save up to 20% of energy

Mini sliding basket A small rack that can slide freely on top of the upper basket. A smart solution to load your dishwasher with more flexibility.

Sliding door For all types of installation in your kitchen.

GENERAL	
Brand	DE DIETRICH
Commercial code	DCJ422Q SX
EAN code	3660767984493
Customs code	84221100

FEATURES	
Type of construction	Built-in
Quantity of cutlery	14
Type of engine	Induction
Tub material	Stainless steel
Drying system	Nat. conv. with auto disconnectable door opening
3 in 1 function	Yes
Colour	
Door colour	Door covering not provided
Panel colour	Stainless steel
Interior light	No
Connectivity	No

PERFORMANCE	
Energy efficiency class	C
Annual energy consumption x100 cycles (kWh)	75
Duration of program (min)	220
Water consumption (L/cycle)	9,8
Noise level (dB (A))	42
Class of environmental noise emissions	B

PROGRAMMING	
Electronic type	Digits
Type of buttons	Touch-sensitive
Keyboard locking	Yes
Delayed start (hr)	24
Remaining time display (hr)	Yes
End of cycle indicator	Spotlight;Buzzer
Number of programmes	8
Programmes	Intensive;Eco;ICS+;90 min;Rapid 30 min;Glass;Universal;Prewash
Options	Half load;Express;Drying Plus;Boost;Energy saving
Number of washing temperatures	5
Temperatures (°C)	45;50;55;60;65
Salt light indicator	Yes
Rinse aid light indicator	Yes

INTERIOR EQUIPMENT	
Upright adjustable upper basket	Yes
Type of lower basket	Modular
3rd basket	Small sliding basket
Cutlery basket	Yes
Equipment for upper basket	1 cup holder;1 holder for stemmed glasses + cups
Maximum size of plate in lower basket (mm)	300
Maximum size of plate in upper basket (mm)	250

De Dietrich

Dishwasher

Ref.: DCJ422Q5X

SAFETY

Hydraulic safety	Overflow+antileakage+Aquablock
------------------	--------------------------------

INSTALLATION

Dimensions of the unboxed product HxWxD (mm)	815X598X550
Dimensions of the packed product HxWxD (mm)	890X645X645
Gross weight (kg)	46
Net weight (kg)	39.5
Removable top	No
Height without the top (mm)	
Adjustable feet	Yes
Back feet adjustable from the front	Yes
Built-in dimensions HxWxD (mm)	820X600X580
Installation at height possible	Yes
Door assembly	Sliding door
Maximum weight supported by the front panel of the unit (kg)	10
Maximum power (W)	1930
Voltage (V)	230
Frequency (Hz)	50
Fuse (A)	10
Plug type	Europe
Hot water and cold water connection	

MANUFACTURING

Country of origin	China
Availability of spare parts (years)	15
Repair Index	9,3
Registration No.	2264689
URL EPREL	https://eprel.ec.europa.eu/qr/2264689

