

De Dietrich

Dishwasher

Ref.: DCJ532DQX



Product highlights

15 Place-setting Your dishwasher has an even bigger capacity thanks to its 3rd very ingenious basket. This drawer dedicated to the wash of flatware is ergonomic and completely flexible; it allows to free space for stemmed glasses.

Inverter motor A high-performance, quieter and long-lasting motor.

ICS+ Intelligent Control System: thanks to sensors, this program adapts throughout the cycle all the parameters of wash (duration, water, temperature) according to the quantity of dishes and its level of dirtiness. The result is then always perfect.

GENERAL

Brand	DE DIETRICH
Commercial code	DCJ532DQX
EAN code	3660767978874
Customs code	84221100

FEATURES

Construction type	Built-in
Quantity of cutlery	15
Type of engine	Induction
Tube material	Stainless steel
Drying system	Natural conv.with auto door opening
3 in 1 function	Yes
Body colour	
Door colour	Door covering not provided
Panel colour	Stainless steel
Interior light	No
Connectivity	No

PERFORMANCE

Energy efficiency class	C
Annual energy consumption x100 cycles (kWh)	76
Duration of program (min)	198
Water consumption (L/cycle)	9,8
Noise level (dB (A))	42
Class of environmental noise emissions	B

PROGRAMMING

Electronic type	Digits
Type of buttons	Touch-sensitive
Keyboard locking	No
Delayed start (hr)	24
Remaining time display (hr)	Yes
End of cycle indicator	Spotlight + buzzer
Number of programmes	8
Programmes	Intensive;Eco;ICS+;90 min;Rapid 30 min;Glass;Universal;Prewash
Options	Half load;Express;Drying Plus;Boost;Energy saving
Number of washing temperatures	5
Temperatures (°C)	40;45;55;60;65
Salt light indicator	Yes
Rinse aid light indicator	Yes

INTERIOR EQUIPMENT

Upright adjustable upper basket	Yes
Type of lower basket	Modular
3rd basket	Yes
Cutlery basket	No
Equipment for upper basket	1 cup holder;1 holder for stemmed glasses + cups
Maximum size of plate in lower basket (mm)	300
Maximum size of plate in upper basket (mm)	250

De Dietrich

Dishwasher

Ref.: DCJ532DQX

SAFETY

Hydraulic safety	Overflow+antileakage+Aquablock
------------------	--------------------------------

INSTALLATION

Dimensions of the unboxed product HxWxD (mm)	815X598X550
Dimensions of the packed product HxWxD (mm)	890X645X645
Gross weight (kg)	50.5
Net weight (kg)	43.5
Removable top	No
Height without the top (mm)	
Adjustable feet	Yes
Back feet adjustable from the front	Yes
Built-in dimensions HxWxD (mm)	820X600X580
Installation at height possible	No
Door assembly	Standard
Maximum weight supported by the front panel of the unit (kg)	10
Maximum power (W)	1930
Voltage (V)	230
Frequency (Hz)	50
Fuse (A)	10
Plug type	Europe
Hot water and cold water connection	

MANUFACTURING

Country of origin	China
Availability of spare parts (years)	15
Repair Index	7,2
Registration No.	1194608
URL EPREL	https://eprel.ec.europa.eu/qr/1194608

