

De Dietrich

Dishwasher

Ref.: DKFI44QSB



Product highlights

Turbo Fan A fan ensures the circulation of the air allowing the dissipation of the vapor and avoiding any track of water at the end of cycle.

Inverter motor A high-performance, quieter and long-lasting motor.

GENERAL

Brand	DE DIETRICH
Commercial code	DKFI44QSB
EAN code	3660767988873
Customs code	84221100

FEATURES

Construction type	Built-in
Quantity of cutlery	14
Type of engine	Induction
Tub material	Stainless steel
Drying system	Air-vented drying system
3 in 1 function	Yes
Body colour	
Door colour	Door covering not provided
Panel colour	Black
Interior light	No
Connectivity	No

PERFORMANCE

Energy efficiency class	D
Annual energy consumption x100 cycles (kWh)	85
Duration of program (min)	254
Water consumption (L/cycle)	9
Noise level (dB (A))	44
Class of environmental noise emissions	B

PROGRAMMING

Electronic type	Digits
Type of buttons	Micro switch
Keyboard locking	No
Delayed start (hr)	19
Remaining time display (hr)	Yes
End of cycle indicator	Spotlight + buzzer
Number of programmes	8
Programmes	Masterwash; iCS+; Hygiene Plus; Eco; Express 14 min; Rapid 30 min; Steam wash; Super 50 mn
Options	Delayed start; Half load; Express; Night silence; Drying Plus
Number of washing temperatures	6
Temperatures (°C)	30;40;50;60;65;70
Salt light indicator	Yes
Rinse aid light indicator	Yes

INTERIOR EQUIPMENT

Upright adjustable upper basket	Yes
Type of lower basket	Modular
3rd basket	No
Cutlery basket	Yes
Equipment for upper basket	1 holder for cutlery; 2 cup holders
Maximum size of plate in lower basket (mm)	300
Maximum size of plate in upper basket (mm)	250

Dishwasher

Ref.: DKFI44QSB

SAFETY

Hydraulic safety	Overflow+antileakage
------------------	----------------------

INSTALLATION

Dimensions of the unboxed product HxWxD (mm)	820X598X550
Dimensions of the packed product HxWxD (mm)	851X644X661
Gross weight (kg)	40
Net weight (kg)	38
Removable top	No
Height without the top (mm)	
Adjustable feet	Yes
Back feet adjustable from the front	Yes
Built-in dimensions HxWxD (mm)	820X600X580
Installation at height possible	No
Door assembly	Sliding door
Maximum weight supported by the front panel of the unit (kg)	8
Maximum power (W)	1900
Voltage (V)	230
Frequency (Hz)	50
Fuse (A)	10
Plug type	Europe
Hot water and cold water connection	

MANUFACTURING

Country of origin	Turkey
Availability of spare parts (years)	15
Repair Index	7,6
Registration No.	1361640
URL EPREL	https://eprel.ec.europa.eu/qr/1361640

