

De Dietrich

Gas hob

Ref.: DPE7620XF



Product highlights

Ergonomics The front controls are ergonomically designed for both right- and left-handed users. The shape of the levers provides an excellent grip for precise adjustments.

Prestige This gas hob features cast iron pot rests - robust and durable -, a visible sign of first-class quality.

Safe cooking This hob is equipped with a thermo-electric flame failure feature, which automatically interrupts the gas supply should the flame be blown out by a draft.

GENERAL

Brand	DE DIETRICH
Commercial code	DPE7620XF
EAN code	3660767964600
Customs code	73211190

FEATURES

Construction type	Built-in
Hob type	Gas
Top material	Stainless steel/black enamel
Width (cm)	60
Energy type	Gas
Type of gas by default	Natural 20 mbar
Alternative gas type	Butane / Propane
Delivered injectors	
Colour	Black
Number of gas burners	4
Control type	Knobs
Control colours	Black/Copper
Ignition system	Integrated
Type of supporting grids	Multiple burners
Number of grids	2
Grid material	Cast iron
Connectivity	



PERFORMANCE

	Cooking zone A	Cooking zone B	Cooking zone C	Cooking zone D
Number of cooking zone	1	2	1	
Type of heating element	Gas (Rapid)	Gas (Semi-rapid)	Gas Auxiliary)	
Position of heating element	Front left	Rear left;Rear right	Front right	
Burner Cap Material	Enamelled cast iron	Enamelled cast iron	Enamelled cast iron	
Dimensions of the heating element (mm)	95	70	50	
Max. power of the heating element in W	3000	1750	1000	
Energy efficiency of gas burner (EE)				

ACCESSORIES

De Dietrich

Gas hob

Ref.: DPE7620XF

SAFETY	
Yes supplied	Seal;Built-in kit
Gas safety device	Thermocouple

INSTALLATION	
Hob maximum gaz power input (kW)	7,5
Fuse (A)	10
Voltage (V)	220-240
Frequency (Hz)	50
Dimensions of the unboxed product HxWxD (mm)	84X590X508
Dimensions of the packed product HxWxD (mm)	135X670X560
Worktop cut-out dimensions WxD (mm)	560X480
Length of power supply cord (cm)	100
Plug type	Without
Net weight (kg)	10.2
Gross weight (kg)	11.4

MANUFACTURING	
Country of origin	Italy
Availability of spare parts (years)	15
Repair Index	