

# De Dietrich

## Dishwasher

Ref.: DVC1434J2



## Product highlights

**Auto Open Door Disconnect** Possibility to disconnect the automatic door opening system to protect any type of work surface.

**14 place settings 3 racks** Thanks to its third rack, which can be adjusted to a half-rack version with a single slide of the hand, your dishwasher can optimise your loads according to your needs. Your flute glasses can be washed at the same time as large pots and pans.

**ICS+** Intelligent Control System: thanks to sensors, this program adapts throughout the cycle all the parameters of wash (duration, water, temperature) according to the quantity of dishes and its level of dirtiness. The result is then always perfect.

GENERAL	
Brand	DE DIETRICH
Commercial code	DVC1434J2
EAN code	3660767984462
Customs code	84221100

FEATURES	
Construction type	Built-in
Quantity of cutlery	14
Type of engine	Standard
Tub material	Stainless steel
Drying system	Natural conv.with auto door opening
3 in 1 function	No
Body colour	
Door colour	Door covering not provided
Panel colour	Black
Interior light	No
Connectivity	No

PERFORMANCE	
Energy efficiency class	D
Annual energy consumption x100 cycles (kWh)	85
Duration of program (min)	198
Water consumption (L/cycle)	10
Noise level (dB (A))	44
Class of environmental noise emissions	B

PROGRAMMING	
Electronic type	Leds
Type of buttons	Micro switch
Keyboard locking	No
Delayed start (hr)	12
Remaining time display (hr)	No
End of cycle indicator	Spotlight + buzzer
Number of programmes	6
Programmes	Intensive;Eco;ICS+;60 min;Rapid 30 min;Glass
Options	Half load
Number of washing temperatures	4
Temperatures (°C)	40;50;55;65
Salt light indicator	Yes
Rinse aid light indicator	Yes

INTERIOR EQUIPMENT	
Upright adjustable upper basket	Yes
Type of lower basket	Modular
3rd basket	Yes
Cutlery basket	No
Equipment for upper basket	1 cup holder;1 holder for stemmed glasses + cups
Maximum size of plate in lower basket (mm)	300
Maximum size of plate in upper basket (mm)	250

## Dishwasher

Ref.: DVC1434J2

### SAFETY

Hydraulic safety	Overflow+antileakage+Aquablock
------------------	--------------------------------

### INSTALLATION

Dimensions of the unboxed product HxWxD (mm)	815X598X550
Dimensions of the packed product HxWxD (mm)	890X645X645
Gross weight (kg)	46
Net weight (kg)	39.5
Removable top	No
Height without the top (mm)	
Adjustable feet	Yes
Back feet adjustable from the front	Yes
Built-in dimensions HxWxD (mm)	820X600X580
Installation at height possible	No
Door assembly	Standard
Maximum weight supported by the front panel of the unit (kg)	7
Maximum power (W)	1930
Voltage (V)	230
Frequency (Hz)	50
Fuse (A)	10
Plug type	Europe
Hot water and cold water connection	

### MANUFACTURING

Country of origin	China
Availability of spare parts (years)	15
Repair Index	7
Registration No.	997310
URL EPREL	<a href="https://eprel.ec.europa.eu/qr/997310">https://eprel.ec.europa.eu/qr/997310</a>

